




"C 100" SERIES

The "C100" series is a range of thirteen transformer clamps with all the advantages of our old "C30" series clamps whilst incorporating considerable improvements, particularly in the field of safety, ergonomics and performance:

- 1,000 A measurement, excellent metrology, high accuracy, high level of linearity, symmetrical coil windings for minimum phase shift, pendular adjusting system for magnetic elements, maximum conductor diameter Ø 52 mm and also some models with μ metal core specially made for wattmeter use.
- Innovative design: excellent ergonomics, handle with finger grips, assisted opening system for jaws (patented system), IEC 1010 600 V cat. III safety (industry and services), antislip protection, conductor anti-pinching system,...

All this technology and manufacturing quality has been combined to provide the best measurement possible without any complications.

A "C100" series clamp is compatible with any instrument (multimeter, wattmeter, recorder, oscilloscope...) for safe measurement of AC currents without shutting down the installation.



Current clamp for AC current

Model C122

C100 series

Current	1,000 A
Ratio	1000/5
Output	5 mA/A

DESCRIPTION

An electronic voltage-limiting system protects output of clamp when operating, if the secondary circuit is opened accidentally.

ELECTRICAL SPECIFICATIONS

- Current range:**
1 A AC .. 1,200 A AC
- Current transformation ratio:**
1000:5
- Output signal:**
5 mA AC / A AC (5 A for 1,000 A)
- Accuracy and phase shift ⁽¹⁾:**


Primary current	1 A .. 20 A	20 A	50 A ⁽²⁾	200 A ⁽²⁾	1,000 A ⁽²⁾	1,200 A ⁽²⁾
Accuracy en %	≤ 6 % + 0.5 mA	≤ 5 %	≤ 3 %	≤ 1.5 %	≤ 1 %	≤ 1 %
Phase shift	not specified	≤ 3°	≤ 3°	≤ 1.5°	≤ 1°	≤ 1°

- Bandwidth:**
30 Hz .. 10 kHz
- Crest factor:**
≤ 6 for a current ≤ 3,000 A peak (500 A_{RMS})
- Maximum currents:**
1,000 A continuous for a frequency ≤ 1 kHz (limitation proportional to the inverse of frequency beyond)
1,200 A for 30 minutes max (interval between measurements > 15 minutes)
- Load impedance:**
≤ 0.6 Ω
- Impedance of connection leads:**
≤ 40 mΩ
- Maximum output voltage (secondary open):**
Electronic protection circuit limiting voltage to 30 V peak max
- Operating voltage:**
600 V_{RMS}
- Common mode voltage:**
600 V category III and pollution degree 2
- Influence of adjacent conductor:**
≤ 1 mA/A at 50 Hz
- Influence of conductor position in jaws:**
≤ 0.2 % of output signal for frequencies ≤ 400 Hz
- Load influence:**
From 0.2 Ω to 0.6 Ω
< 0.5 % on measurement
< 0.5° on phase
- Influence of frequency ⁽³⁾:**
< 1 % of output signal from 30 Hz .. 48 Hz
< 0.5 % of output signal from 65 Hz .. 1 kHz
< 1 % of output signal from 1 kHz .. 5 kHz

- Influence of crest factor:**
< 1 % of output signal for crest factor ≤ 6 with current ≤ 3,000 A peak (500 A_{RMS})
- Influence of DC current superimposed on rated current:**
< 1 % of output signal for a current ≤ 30 A DC

MECHANICAL SPECIFICATIONS

- Operating temperature:**
-10 °C to +50 °C
- Storage temperature:**
-40 °C to +70 °C
- Influence of temperature:**
≤ 0.1 % of output signal per 10 °K
- Relative humidity for operation:**
0 to 85 % RH with a linear decrease above 35 °C
- Influence of relative humidity:**
< 0.2 % of output signal from 10 % to 85 % RH
- Operating altitude:**
0 to 2,000 m
- Max. jaw opening:**
53 mm
Patented progressive opening system
- Clamping capacity:**
 - Cable: Ø max 52 mm
 - Busbar: 1 busbar of 50 x 5 mm / 4 busbars of 30 x 5 mm
- Casing protection rating:**
IP40 (IEC 529)
- Drop test:**
1 m (IEC 68-2-32)



- Shock resistance:**
100 g (IEC 68-2-27)
- Vibration resistance:**
5/15 Hz 1.5 mm
15/25 Hz 1 mm
25/55 Hz 0.25 mm (IEC 68-2-6)
- Self-extinguishing capability:**
Casing and jaws: UL94 V0
- Dimensions:**
216 x 111 x 45 mm
- Weight:**
550 g
- Colours:**
Dark grey case with red jaws
- Output:**
Safety sockets (4 mm)

SAFETY SPECIFICATIONS

- Electrical safety:**
Instrument with double insulation or reinforced insulation between the primary the secondary and the grippable part located under the guard as per IEC 1010-1 & IEC 1010-2-032
- 600 V category III, pollution degree 2
- 300 V category IV, pollution degree 2
- Electromagnetic compatibility (EMC):**
EN 50081-1: class B
EN 50082-2:
- Electrostatic discharge: IEC 1000-4-2
- Radiated field: IEC 1000-4-3
- Fast transients: IEC 1000-4-4
- Magnetic field at 50/60 Hz: IEC 1000-4-8

(1) Conditions of reference: 23 °C ± 3 °K, 20 % to 75 % RH, signal sinus, frequency of 48 Hz to 65 Hz, distortion factor < 1 %, no DC components, external magnetic field < 40 A/m, no AC magnetic field, conductor centred for measurement, load impedance 0.2 Ω (5 VA)

(2) Accuracy class in accordance with IEC 185: 5 VA - class 1 - 48 .. 65 Hz

(3) Out of reference domain

To order	Reference
AC current clamp model C122 with operating manual	P01120306